

DECLARATION OF COMPLIANCE Ultipleat® High Flow Filter Elements UY Series “W” Code

Element Part Number

HFU 6 J U W
Table 1 Table 2

This is a guide to the part numbering structure only. For specific options, please contact Pall.

Table 1 : Nominal Length

Code	Description
20	508 mm (20")
40	1016 mm (40")
60	1524 mm (60")

Table 2 : Removal Rating

Code	Description
UY020	2 µm
UY045	4.5 µm
UY100	10 µm
UY200	20 µm
UY400	40 µm

The Ultipleat High Flow filter element is a disposable, pleated, coreless filter designed for high flow rates in food contact use, at temperatures up to 50 °C (122 °F).

An initial flush is recommended prior to use.

Issued 1 August 2009
 Revised 13 October 2017
 Expires 28 February 2019
 Reference FBDCUHFENj
 Page 1 of 3



Mark A. Harris
 Quality Manager
 Pall Cortland

Ultipleat High Flow Filter Elements (UY Series “W” Code)

Components

Filter Media	Proprietary melt blown polypropylene Profile® UP media
Support Mesh and Outer Wrap	Polypropylene
Wrap Adhesive	Hot air bonding
End Caps and Handle	White (TiO ₂) filled) colored polypropylene moldings (10 % glass reinforced)
O-ring Seal	Ethylene Propylene Rubber (EPR)

Declaration

Ultipleat High Flow UY Series filter elements comprise materials that meet regulatory and legislative requirements and guidelines for food contact in that:

Europe

The “W” Code UY Series Ultipleat High Flow filter elements meet the requirements for food contact as detailed in European Regulation (EC) Number 1935/2004 in that:

- Our suppliers’ information indicates that the polymeric materials used to produce “W” Code UY Series Ultipleat Profile type products employing Profile UP media are made from monomers and additives consistent with Annex I of Commission Regulation (EU) Number 10/2011 and its amendments, relating to plastic materials and articles intended to come into contact with foodstuffs.
- Overall Migration Limit testing of Profile UP filter media, HFU hardware components and support mesh has been performed after flushing and in flow conditions (excluding seals) in:
Simulant A (10% ethanol) at 100 °C (212 °F) for 4 hours
Simulant B (3% acetic acid) at 100 °C (212 °F) for 4 hours
Distilled water at 100 °C (212 °F) for 4 hours

SML testing of a typical UY filter pack has been conducted after flushing and in flow conditions in:

Simulant A (10% ethanol) at 50 °C (122 °F) for 2 hours
Simulant B (3% acetic acid) at 50 °C (122 °F) for 2 hours
Distilled water at 50 °C (122 °F) for 2 hours

SML testing of support mesh material has been performed after flushing and in flow conditions in:

Simulant A (10% ethanol) at 100 °C (212 °F) for 4 hours
Simulant B (3% acetic acid) at 100 °C (212 °F) for 4 hours
Distilled water at 100 °C (212 °F) for 4 hours

Note:

This product contains materials that are subject to SML requirements.
This product contains calcium stearate, which is approved as a direct food additive.

- Glass fibers are listed as an additive to plastic within European Regulation 10/2011 under reference 55520.

USA

The thermoplastic filter components, with the exception of the glass filler in the molded end caps, meet the FDA requirements for contact use as detailed in Code of Federal Regulations, 21 CFR paragraphs 170-199 in that:

- The molded end caps utilize a glass-filler to enhance the strength and maintain dimensional stability.
- Polypropylene to 21 CFR section 177.1520 (Olefin polymers) and section 178.2010 (antioxidants and/or stabilizers for polymers)
- Ethylene Propylene Rubber and Silicone Elastomeric seal materials to 21 CFR section 177.2600 (Rubber articles intended for repeated use, excluding milk and edible oils)

Process Quality System

Site of Manufacture: Pall Cortland, USA

The Quality Management System at Pall Cortland is certified to ISO 9001:2008.

These products / product packaging carry a lot number / date code to facilitate traceability to suppliers' materials and Pall production records.

Supplied in Europe by

Pall International Sàrl
Av. de Tivoli 3
Fribourg
Switzerland
CH-1700




Pall Food and Beverage

New York - USA
+1 516 484 3600 telephone
+1 866 905 7255 toll free
foodandbeverage@pall.com

Visit us on the web at www.pall.com

Pall Corporation has offices throughout the world. For Pall representatives in your area, please go to www.pall.com/contact.

Because of developments related to products, systems and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid.

© Copyright 2017, Pall Corporation. Pall, , Profile and Ultipleat are trademarks of Pall Corporation. ® indicates a trademark registered in the USA. Filtration.Separation.Solution is a service mark of Pall Corporation.